

3 ft Mini DisplayPort™ to DVI Adapter Converter Cable – Mini DP to DVI 1920x1200 - White

StarTech ID: MDP2DVIMM3W



The MDP2DVIMM3W Mini DisplayPort® to DVI Adapter Cable lets you directly connect your Mini DP video source (Desktop PC, Laptop, Ultrabook etc.) to a DVI monitor, projector, eliminating the expense of having to upgrade to a Mini DisplayPort-capable monitor.

The adapter cable is 3 feet (1 m) in length, and features male-to-male connectors, allowing you to connect your Mini DisplayPort source directly to a DVI display with no additional cabling required.

Compatible with Intel® Thunderbolt™, when connected directly to a supporting DisplayPort over Thunderbolt™ I/O port, the adapter supports resolutions up to 1920x1200 (WUXGA).

MDP2DVIMM3W is a passive adapter that requires a dual-mode DisplayPort port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connect your existing DVI display device (monitor, projector) to a Mini DisplayPort output device
- Ideal for using your DVI monitor as a secondary display





Features

- 1x Male Mini DisplayPort connector, 1x Male DVI connector
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal

Technical Specifications

Warranty 2 Years

Adapter Style Cable Adapter

Audio No

Chipset ID NXP 3361
Converter Type Passive

Output Signal DVI-D (DVI Digital)

Connector A 1 - Mini-DisplayPort (20 pin) Male

Connector B 1 - DVI-D (25 pin) Male

Maximum Cable Length 3 ft [0.9 m]

Maximum Digital 1920x1200 / 1080p

Resolutions

Wide Screen Supported Yes

System and Cable DP++ (DisplayPort++) port required from video card or video source for DVI and

Requirements HDMI® signal pass-through

Cable Length 3 ft [0.9 m]

Color Black

Product Height 0.6 in [15 mm]
Product Length 36 in [914 mm]
Product Weight 2.6 oz [75 g]
Product Width 1.6 in [40 mm]
Humidity 40%-85%RH

Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature 0°C to 70°C (32°F to 158°F)

Shipping (Package) 3 oz [86 g]

Weight

Included in Package 1 - Mini DisplayPort® to DVI Adapter





Certifications, Reports and Compatibility





