

2 Port USB DisplayPort® Cable KVM Switch w/ Audio and Remote Switch - USB Powered

StarTech ID: SV211DPUA



The SV211DPUA 2-Port DisplayPort® Cable KVM Switch with Audio and Remote Switching Control lets you control two DisplayPort, USB equipped PCs with a single monitor, keyboard, mouse and audio peripheral set.

To help organize your desk without sacrificing work space, this compact DisplayPort USB KVM features integrated cables that can be connected directly to your system, while leaving a minimal footprint. The switch features a remote push-button on a 1.5 meter (5ft) integrated cable that can be placed in an easily accessible location, as well as keyboard hot-keys, and PC or Mac® compatible software for switching between systems. To eliminate the need for a bulky external power adapter and wall outlet, the DisplayPort KVM switch is USB-powered.

This KVM with DisplayPort video capability offers support for resolutions up to 2560x1600 for the ability to drive a large DisplayPort display for applications that require high graphical output.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Great for PC test/burn-in computer control, saving the desk space required for two monitors, keyboards and mice
- Perfect for sharing computers and attached peripherals in the home or home office
- Dual system control for single user workstations increasing user productivity in the office

Features

- Supports resolutions up to 2560x1600
- Switch PCs via push-button, hot-keys or switching software
- Space-saving design, minimal footprint
- Integrated KVM cables and remote switch
- Switching software supports PC and Mac® platforms
- USB Powered - No external power adapter required
- Independent audio/mic switching for uninterrupted audio
- Analog (3.5mm) and DisplayPort audio supported
- Supports hot-plugging
- Remote switch on 1.5m (5ft.) cable

Technical Specifications

| | |
|------------------------|---|
| Warranty | 2 Years |
| Audio | Yes |
| Cables Included | Yes |
| Daisy-Chain | No |
| KVM Ports | 2 |
| Multi-Monitor | No |
| PC Interface | USB |
| PC Video Type | DisplayPort |
| Rack-Mountable | No |
| Audio Specifications | Analog (3.5mm) and DisplayPort audio supported |
| IP Control | No |
| Port Selection Support | Push Button, Hotkeys, and Software |
| Console Interface(s) | 1 - DisplayPort (20 pin) Female |
| Console Interface(s) | 2 - 3.5 mm Mini-Jack (3 Position) |
| Console Interface(s) | 2 - USB A (4 pin) |
| Host Connectors | 1 - DisplayPort (20 pin) Latching Male |
| Host Connectors | 1 - USB A (4 pin) Male |
| Host Connectors | 2 - 3.5 mm Mini-Jack (3 Position) Male |
| OS Compatibility | Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64), 2000 Windows Server® 2012, 2008 R2, 2003(32/64) Mac OS 10.x (Tested up to 10.9), 9.x |
| Note | OS Compatibility refers to KVM software only - the KVM itself can be used without software on any platform |
| Cable Length | 33.5 in [850 mm] |
| Color | Black |
| Enclosure Type | Plastic |
| Product Height | 0.9 in [23 mm] |
| Product Length | 3.5 in [88 mm] |
| Product Weight | 14.1 oz [400 g] |
| Product Width | 2.6 in [66 mm] |
| LED Indicators | 1 - PC Selection indicator |
| Power Source | USB-Powered |
| Humidity | 0~90% RH Non-Condensing |

| | |
|---------------------------|------------------------------|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -20°C to 60°C (4°F to 140°F) |
| Shipping (Package) Weight | 19.4 oz [550 g] |
| Included in Package | 1 - KVM Switch |
| Included in Package | 1 - Software CD |
| Included in Package | 1 - Instruction Manual |

Certifications, Reports and Compatibility

