

# USB-C to HDMI Adapter Cable - 2m (6 ft.) - 4K at 30 Hz

Product ID: CDP2HDMM2MB



This USB-C<sup>™</sup> to HDMI® adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type-C<sup>™</sup> device to your HDMI monitor, television or projector. The adapter supports a connection distance of up to 2 m (6 ft.) and works with USB-C devices that support DP alt mode, such as the MacBook, ChromeBook Pixel<sup>™</sup> and Dell<sup>™</sup> XPS<sup>™</sup> models 15 and 13. It's also compatible with Thunderbolt<sup>™</sup> 3 ports.

## **Clutter-free installation**

At 2 m (6 ft.) in length, this adapter cable delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For shorter installations, we also offer a 1 m (3 ft.) USB-C to HDMI cable, enabling you to choose the right cable length for your custom installation needs.

www.startech.com 1 800 265 1844



## **Data Sheet**

## Hassle-free connection with USB Type-C

The adapter cable is easy to connect, through the versatility and convenience of the USB Type-C port on your device. USB-C is a reversible connector, so it doesn't matter which way you plug it in, the adapter will always connect. This saves you the frustration of trying to insert it correctly when you're docking your computer to your workstation or office hot desk.

## Astonishing picture quality

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K monitor or television. This adapter cable lets you harness the video capabilities that are built into your USB Type-C connection to deliver the astonishing quality of Ultra HD to your 4K display.

The adapter is backward compatible with 1080p displays, ensuring the adapter will also work for HD applications at your home or office.

The CDP2HDMM2MB is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Note:

Your USB-C equipped device must support video (DP alt mode) to work with this adapter.

www.startech.com 1 800 265 1844



# **Data Sheet**

#### Certifications, Reports and Compatibility









#### Applications

- Connect a USB Type-C computer to an HDMI projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your HDMI display

#### Features

- Reduce clutter with a compact 2 m (6 ft.) adapter cable
- Hassle-free connection with the reversible USB-C connector
- Astonishing video quality with support for video resolutions up to 4K at 30 Hz
- Plug-and-play installation
- No power adapter required
- Thunderbolt 3 port compatible

www.startech.com 1 800 265 1844



Hard-to-find made easy\*

# **Data Sheet**

	Warranty	2 Years
Hardware	Adapter Style	Cable Adapters
	AV Input	USB Type-C
	AV Output	HDMI
	Chipset ID	Parade - PS171 NXP - PTN5100
	Ports	1
Performance	Audio Specifications	7.1 surround sound
	Maximum Analog Resolutions	1920x1200 or 1080p
	Maximum Digital Resolutions	3840x2160 @ 30 Hz
	Supported Resolutions	1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K)
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
		1 UDMI (10 min) Mala Output
	Connector B	1 - HDMI (19 pin) Male Output
	System and Cable Requirements	
Requirements		Your USB-C port must support DisplayPort over USB-C (DF
Requirements	System and Cable Requirements	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Requirements	System and Cable Requirements Humidity	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 5%-90% RH (no condensation)
Requirements Environmental Physical	System and Cable Requirements Humidity Operating Temperature	Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F)
Requirements Environmental Physical	System and Cable Requirements Humidity Operating Temperature Storage Temperature	Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F)
Special Notes / Requirements Environmental Physical Characteristics	System and Cable Requirements Humidity Operating Temperature Storage Temperature Accent Color	Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) Black
Requirements Environmental Physical	System and Cable RequirementsHumidityOperating TemperatureStorage TemperatureAccent ColorCable Length	Your USB-C port must support DisplayPort over USB-C (DF Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) Black 6.6 ft [2 m]

Product appearance and specifications are subject to change without notice.