ASUS uses cookies and similar technologies to perform essential online functions, analyze online activities, provide advertising services and other functions. For detailed information, please visit "Cookies and similar technologies".

**Cookie Settings** 

**Accept Cookies** 

**Products** 

What's Hot

Commercial

Service

#### P11C-X

### Processor / System Bus1 x Socket LGA1151

Intel® Xeon® processor E-2100 family(95W)

Intel<sup>®</sup> Core<sup>™</sup> i3 processors

Intel<sup>®</sup> Pentium<sup>™</sup> processors

Intel<sup>®</sup> Celeron<sup>™</sup> processors

\*Refer to support page for more information

## Core LogicIntel® C242 Chipset

MemoryTotal Slots: 4 (2-channel)
Capacity: Maximum up to 64GB UDIMM

**Memory Type:** 

DDR4 2666/2400 UDIMM non ECC and with ECC

Memory Size: 16GB, 8GB, 4GB

\* Refer to support page for more information

Expansion SlotsTotal Slot: 4

Slot Location 3 : PCI-E x8 (Gen3 X4 Link)

Slot Location 4 : PCI 32bit/33MHz Slot Location 5 : PCI 32bit/33MHz

Slot Location 6: PCI-E x16 (Gen3 X16 Link)

Follow SSI Location#

#### Form FactorATX (12"x9.6", 305mm x 244mm)

### StorageSATA Controller:

Intel® C242 Chipset

6 x SATA 6Gb/s ports + 2 x M.2 connector \*1

 $Intel @ Rapid Storage Technology Enterprise (RSTe) \ (For Linux/Windows) \\$ 

(Support Software RAID 0, 1, 5, 10)

#### **SAS Controller:**

ASUS PIKE II 3008-8i 8-port SAS 12G RAID card

ASUS PIKE II 3108-8i 8-port SAS 12G HW RAID card

## Networking<sup>1 x Intel®</sup> I210AT

1 x i219-LM

### Graphic Aspeed AST2510 with 64MB VRAM

### On Board I/O1 x TPM header

1 x PSU Power Connector (24-pin ATX power connector + 8-pin ATX 12V power connector)

- 1 x USB 3.0 pin header, Up to 2 Devices
- 2 x USB 2.0 pin header, Up to 3 Devices
- 6 x Fan Header, 4pin
- 1 x Chassis Intruder
- 2 x Front LAN LED
- 1 x Serial Port Header
- 1 x LPT
- 2 x M.2 Connector , NGFF Type : 22110/2280/2260/2242

#### Back I/O Ports1 x PS/2 Keyboard/ Mouse Port

2 x USB 3.1

2 x USB 3.0

2 x USB 2.0

1 x VGA Port (onboard Aspeed AST2510)

2 x RJ45 LAN Ports

# Management Solution ASUS Control Center

### AccessoriesGift Box (1-in-1)

1 x Support DVD

1 x I/O shield

6 x SATA 6G cables

1 x Plate for LGA1151

1 x ASUS Control Center Quick Guide

Bulk Pack (10-in-1)

1 x Support DVD

1 x I/O shield

1 x Plate for LGA1151

1 x ASUS Control Center Quick Guide

#### Note\*1

Intel® C242:

6 \* SATA 6Gb/s ports with 2 \* M.2 (NGFF 22110/2280/2260/2242, gray SATA port will disable when M.2 is SATA signal)\*\*

\*\* One supports both SATA 6Gb/s & PCI-E Gen3 x2 link, the other is SATA 6Gb/s only.

- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.

Terms of Use Notice | Privacy Policy | ©ASUSTeK Computer Inc. All rights reserved.

• The information contained is general testing result for reference. Please consult local sales representative for more information on specific supported CPU list on each system.

Want More?
Who We Are
Need Help?
Community
Global / English