

## VT229H

**Display Panel Size:** Wide Screen 21.5"(54.6cm) 16:9

**Panel Type :** IPS

**True Resolution :** 1920x1080

**Display Viewing Area(HxV) :** 476.64 x 268.11 mm

**Full HD 1080P :** Yes

**Display Surface**Glare, 7H Hardness

**Pixel Pitch :** 0.2482 mm

**Brightness(Max) :** 250 cd/m<sup>2</sup>

**Contrast Ratio (Max) :** 1000:1

**ASUS Smart Contrast Ratio (ASCR) :** 100000000:1

**Viewing Angle (CR<sub>≥</sub>10) :** 178°(H)/178°(V)

**Response Time :** 5ms (Gray to Gray)

**Display Colors :** 16.7M

**Flicker free**

**Touch Screen :** Yes, Capacitive 10-point multi-touch

**Touch Glass Thickness:** 1.1 mm

**Video Feature****Trace Free Technology :** Yes

**SPLENDID Video Preset Modes :** 8 Modes (sRGB Mode/Scenery

Mode/Theater Mode/Standard Mode/Night View Mode/Game

Mode/Reading Mode/Darkroom Mode)

**Skin-Tone Selection :** 3 Modes

**Color Temperature Selection :** 4 Modes

**QuickFit (modes) :** Yes (Alignment Grid/Photo Modes)

**Low Blue Light :** Yes

**HDCP support :** Yes

**VividPixel :** Yes

**Audio Features****Stereo Speakers :** 1.5W x 2 Stereo RMS

**I/O Ports****Signal Input :** HDMI, D-Sub

**PC Audio Input :** 3.5mm Mini-Jack

**USB Port(s) :** 2.0x1, \*1

**Signal Frequency** Analog Signal Frequency : 30~83 KHz(H)/ 50~75 Hz(V)

**Digital Signal Frequency** : 30 ~83 KHz (H) /50 ~75 Hz(V)

**Power Consumption** Power On : <21.9W (\*2)

Power Saving/Off : <0.5W

100-240V, 50/60Hz

**Mechanical Design** Chassis Colors : Black

Tilt : +20°~-5°

**VESA Wall Mounting** : 100x100mm

**Security** Kensington lock

**Dimensions** Phys. Dimension with Stand(WxHxD): 491.5 x 300.1 x 204.4 mm

Phys. Dimension without Stand(WxHxD): 491.5 x 300.1 x 51.9 mm(For VESA Wall Mount)

Box Dimension(WxHxD):558 x 430 x 137 mm

**Weight** Net Weight (Esti.): 3.83 kg; 3.18kg(without Stand)

Gross Weight (Esti.): 6.13kg

**Accessories** VGA cable(Optional)

Audio cable

Power cord

USB cable

Quick start guide

HDMI cable (Optional)

Warranty Card

**Compliance and Standards** Energy Star®, BSMI, CB, CCC, CE, CEL level , ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, RoHS, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 8.1, Windows 7), MEPS, RCM, TUV Flicker-free , KC , eStandby, TUV Low Blue Light

**Note**\*1. for touch signal

\*2. measuring a screen brightness of 200 nits without audio/ USB connection



- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- The actual transfer speed of USB 3.0, 3.1, 3.2, and/or Type-C will vary depending on many factors including the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment.

Want More?

---

Who We Are?

---

Need Help?

---

Community

---

Australia / English

[Privacy Policy](#) | [Terms of Use Notice](#) | ©ASUSTeK Computer Inc. All rights reserved.