



SRV6KRIL



High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions

Includes: CD with software, USB cable, User Manual



Technical Specifications

Output

Output power capacity	6.0kWatts / 6.0kVA
Max Configurable Power (Watts)	6.0kWatts / 6.0kVA
Nominal Output Voltage	230V
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard Wire 3-wire
Other Input Voltages	220, 240

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	600Joules
----------------------------	-----------

[Back to top](#)



Physical

Maximum Height	173MM, 17.3CM
Maximum Width	438MM, 43.8CM
Maximum Depth	710MM, 71.0CM
Net Weight	61.0KG
Shipping weight	71.0KG

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6meters

Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs

Recently viewed



APC Easy UPS SRV RM
6000VA 230V
SRV6KRI

[Back to top](#)

