

ASUS uses cookies and similar technologies to perform essential online functions, analyze online activities, provide advertising services and other functions. For detailed information, please visit "[Cookies and similar technologies](#)".

[Cookie Settings](#)[Accept Cookies](#)[Products](#)[What's Hot](#)[Commercial](#)[Service](#)

## P11C-M/4L

---

### Processor / System Bus

1 x Socket LGA1151  
Intel® Xeon® processor E-2100 family  
Intel® Core™ i3 processors  
Intel® Pentium™ processors  
Intel® Celeron™ processors

### Core Logic

Intel® C242 Chipset

### Memory

**Total Slots :** 4 (2-channel)

**Capacity :** Maximum up to 64GB UDIMM

**Memory Type :**  
DDR4 2666/2400 UDIMM non ECC and with ECC

**Memory Size :**

16GB, 8GB, 4GB

\* Refer to support page for more information

### Expansion Slots

Total Slot : 2  
Slot Location 6 : PCI-E x16 (Gen3 X16 Link), Auto switch to x8 link if slot 7 is occupied

Slot Location 7 : PCI-E x8 (Gen3 X8 Link)

Follow SSI Location#

**Form Factor**U ATX (9.6"x9.6", 244mm x 244mm)

**ASUS Features**FAN speed control  
 Rack Ready (Rack and Pedestal dual use)  
 ASUS Control Center

**StorageSATA Controller :**

Intel® C242 Chipset  
 6 x SATA3 6Gb/s ports  
 2 x M.2 connector(2242/2260/2280/22110) both SATA & PCIe mode \*1  
 Intel® Rapid Storage Technology Enterprise(RSTe) (For Linux/Windows)  
 (Support Software RAID 0, 1, 5, 10 )

**SAS Controller :**

ASUS PIKE II 3008-8i 8-port SAS 12G RAID card(Optional)  
 ASUS PIKE II 3108-8i 8-port SAS 12G HW RAID card(Optional)

**Networking**4 x Intel® I210AT + 1 x Mgmt LAN

**Graphic**Aspeed AST2500 with 32MB VRAM

**On Board I/O**1 x TPM header

1 x PSU Power Connector (24-pin ATX power connector + 8-pin ATX 12V power connector)  
 1 x COM port  
 1 x USB 3.0 pin header , Up to 2 Devices  
 1 x USB 2.0 pin header , Up to 2 Devices  
 1 x USB connector\*2  
 5 x Fan Header , 4pin  
 1 x SMBus  
 1 x Chassis Intruder  
 4 x Front LAN LED  
 1 x Serial Port Header  
 1 x VGA Header  
 2 x M.2 Connector  
 1 x Onboard header for optional management card

**Back I/O Ports**1 x External Serial Port

2 x USB 3.1 Gen 2  
 2 x USB 3.1 Gen 1  
 1 x VGA Port  
 4 x GbE LAN + 1 x Mgmt LAN

**Management Solution**ASUS Control Center

Optional ASMB9-iKVM for KVM-over-Internet

**Environment** Operation temperature: 10°C ~ 35°C  
Non operation temperature: -40°C ~ 70°C  
Non operation humidity: 20% ~ 90% ( Non condensing)

**Weight** Gift Box (1-in-1)  
Net Weight : 0.747 KG  
Gross Weight : 1.3 KG

Bulk Pack (10-in-1)  
Net Weight : 7 KG  
Gross Weight : 8 KG

**Accessories** Gift Box (1-in-1)  
2 x Support CD  
1 x I/O shield  
6 x SATA 6G cables  
1 x Plate for LGA1151

Bulk Pack (10-in-1)  
2 x Support CD  
1 x I/O shield  
1 x Plate for LGA1151

**Monitoring** CPU Temperature  
Fan RPM

**Note**\*1 2 x M.2 (NGFF 22110/2280/2260/2242, support PCIE or SATA signal, gray SATA port will disable when M.2 is SATA signal)  
\*2 1 x USB 3.0 connector (Type A USB socket)

- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.
- The information contained is general testing result for reference. Please consult local sales representative for more information on specific supported CPU list on each system.

Want More?

---

Who We Are

---

Need Help?

---

Community

---

Global / English

[Terms of Use Notice](#) | [Privacy Policy](#) | ©ASUSTeK Computer Inc. All rights reserved.