

# Eaton 5SX UPS



1. Graphical LCD display
2. Panel for batteries replacement (Hot swappable)
3. USB port + Serial port
4. 8 IEC 10A (+1 IEC 16A outlets for 3000VA models)
5. Communication card slot
6. ROO/RPO terminal (Rack and R/T models only)



Affordable protection for networking systems, emergency lighting and electrical infrastructure.

## Manageability

- The LCD interface provides clear status of the UPS key parameters such as input and output voltage, load and battery level, and estimated runtime. Essential configuration capabilities are also offered for output voltage, audible alarm and sensitivity.
- The 5SX offers USB and serial connectivity. USB port is HID compliant for automatic integration into Windows, Mac OS and Linux.
- A slot for an optional communication card (including SNMP/Web card or relay contact card) is available. Eaton's Intelligent Power® Software Suite insures compatibility with all major OS including virtualization software.

## Flexibility

- R/T models authorizes either tower or rack installation -pedestals are included, rail kits are an optional extra. (5SXRACKKIT2U)
- Easy battery replacement from front panel to extend UPS life.
- Up to 4 EBM's can be added for longer runtimes

## Reliability

- Pure sinewave output: When operating in battery mode the 5SX provides a high quality output signal for any sensitive equipment connected.
- Buck and Boost operation corrects a wide range of input voltage variations through continuous regulation, without the use of batteries.
- Stronger, longer battery life: Eaton ABM® battery management technology uses an innovative three-stage charging system that extends battery life by up to 50%.

## Ideal for protecting

- NAS, Network equipment
- ATMs, Ticket machines, Kiosks



Powering Business Worldwide

| <b>Eaton 5SX Technical Specifications</b>            |   |                   |  |
|--|---|-------------------|--|
| <b>Technical Specifications</b>                      | <b>5SX1250AU</b>                          | <b>5SX1750AU</b>  | <b>5SX3000AU</b>                         |
| Rating (VA/W)  | 1250VA/1125W                              | 1750VA/1575W      | 3000VA/2700W                             |
| Format   | RACK, Tower selectable                    |                   |  |
| <b>Electrical Characteristics</b>                    |   |                   |  |
| Technology/output                                    | Line interactive, pure sine wave output   |                   |  |
| Input voltage ranges without using batteries         | 160V - 290V                               |                   |  |
| Output voltage                                       | 240V                                      |                   |  |
| Output Frequency                                     | Auto sensing, 50Hz default                |                   |  |
| <b>Connections</b>                                   |   |                   |  |
| Input  | IEC C14-AU 10A                            | IEC C14-AU 10A    | IEC C20-AU 16A                           |
| Outputs  | 9*IEC C13 outlets                         | 9*IEC C13 outlets | 8*IEC C13 outlets +<br>1*IEC C19 outlets |
| <b>Batteries**</b>                                   |   |                   |  |
| EBM  | 5SXEBM48R2U                               |                   | 5SXEBM72R2U                              |
| 1UPS   | 5min                                      | 3.7min            | 2.4min                                   |
| 1UPS+1EBM  | 23min                                     | 19.4min           | 16.8min                                  |
| 1UPS+2EBM  | 47min                                     | 35min             | 33.7min                                  |
| Battery management                                   | ABM                                       |                   |  |
| <b>Power management</b>                              |   |                   |  |
| Communication Ports                                  | 1 USB port +1 RS232+ 1 communication slot |                   |  |
| Connectivity cards                                   | NETWORK-MS, Relay card                    |                   |  |
| Software   | IPSS                                      |                   |  |
| <b>Operating conditions, standards and approvals</b> |   |                   |  |
| Operating temperature                                | 0-40°C                                    |                   |  |
| Noise level  | <40db                                     |                   |  |
| Regulations  | EN62040-2, EN61000-4                      |                   |  |
| <b>Dimensions D x H x W / Weight</b>                 |   |                   |  |
| Dimensions (mm)                                      | 522*441.2*86.2(2U)                        |                   | 647*441.2*86.2(2U)                       |
| Weight (kg)  | 25.4                                      | 26.6              | 35.3                                     |
| <b>Customer Service &amp; Support</b>                |   |                   |  |
| Warranty   | 2 years                                   |                   |  |

\* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

\*\* Based on 100% load