



APC Smart-UPS 48V 585 Wh LI Battery Pack

XBP48RM1U-LI

Call for More Information +61 2 9125 8951

- Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.
- Includes: 4 post rail kit, Comms cable, Grounding Cable, Installation guide, Rack Mounting brackets

Output

Battery Output Voltage	48
------------------------	----

Batteries & Runtime

Battery type	Lithium Ion
--------------	-------------

Battery mounting	Rack Mount
------------------	------------

Expected Battery Life (years)	5 - 10
-------------------------------	--------

Battery Design Life	--
---------------------	----

Physical

Maximum Height	43MM, 4.3CM
----------------	-------------

Maximum Width	432MM, 43.2CM
---------------	---------------

Maximum Depth	521MM, 52.1CM
---------------	---------------

Rack Height	1U
-------------	----

Net Weight	13.02KG
------------	---------

Shipping weight	18.64KG
-----------------	---------

Shipping Height	200MM, 20.0CM
-----------------	---------------

Shipping Width	600MM, 60.0CM
----------------	---------------

Shipping Depth	850MM, 85.0CM
----------------	---------------

Color	Black with silver front bezel
-------	-------------------------------

Units per Pallet	8.0
------------------	-----

Environmental

Operating Temperature	0 - 40 °C
-----------------------	-----------

Operating Relative Humidity	0 - 95 (no %)
-----------------------------	---------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Environmental	
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %
Storage Elevation	0-15000meters

Conformance	
Approvals	UL 1973
Standard warranty	5 year repair or replace

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.