

4K HDMI over IP Receiver for ST12MHDLAN4K

Product ID: ST12MHDLAN4R



This 4K HDMI® over IP receiver works with the [4K HDMI over IP Extender Kit](#) (sold separately) and lets you extend a 4K HDMI signal, as well as RS-232 peripheral device connections, over your network. You can use additional receivers (sold separately) to distribute the HDMI signal to multiple locations, each with 4K support, and combine your remote displays to create a video wall.

The IP receiver also features RS-232 extension which enables you to add a remote serial operated device at your video source or each remote display. This HDMI over IP extender is the perfect solution for combining a serial-operated touchscreen with your display or video wall, to create interactive digital signage presentations.

Extended scalability

You can add multiple receivers to your HDMI over IP extender kit to create a point-to-multipoint setup or video wall. In these configurations, you can also add additional sources (transmitters) with even more displays (receivers) over your Gigabit Ethernet switch with IGMP. For further scalability, you can combine up to 16 total (transmitters) and as many receivers (displays) as your network bandwidth can support.



The extender also features a separate 3.5 mm audio source that enables you to switch between the native HDMI audio and a separate 3.5 mm audio source, so you can distribute a single audio source to multiple remote locations over IP (also requires a Gigabit Ethernet switch with IGMP).

Ultra HD 4K resolution at 30Hz

This HDMI over IP kit uses H.264 compression to deliver astonishing 4K UHD video to your remote 4K displays over an IP connection. With support for 4K, you can achieve an output resolution of up to 3840 x 2160p at 30Hz, which enables you to extend a 4K video source to multiple remote locations -- perfect for digital signage or entertainment video distribution throughout large buildings such as schools, hospitals, shopping centers or areas.

The extender is backward compatible with lower resolutions such as 1080p or 720p, making it great for lower resolution applications while future-proofing your infrastructure for 4K implementation.

Manage your video distribution from your mobile device

This HDMI distribution kit features an easy-to-use video control software app that helps you manage your IP video distribution. The app is simple to set up, with automatic hardware detection, and it lets you switch video sources for each remote display. You can also create and manage a video wall, for an impressive digital signage presentation that's sure to catch your audience's attention.

The software is available on iOS for your iPhone or iPad, Android™ for your smartphone or tablet, and Google Chrome™ browser.

Professional, cost-effective, simple installation

The HDMI over IP extender kit includes optional slot shelf mounting hardware for a tidy installation. Plus, because the extender uses standard non-proprietary CAT5e or CAT6 Ethernet cable with RJ-45 connectors, it eliminates both the expense and hassle of running specialized cables.

The extender also features an EDID copy function, which ensures native resolution and maximum compatibility with your display or projector for a convenient plug-and-play installation.

Download the StarTech.com Video Control software to manage your IP video distribution.



The ST12MHDLAN4R is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Note: For best performance, a managed network switch with IGMP is recommended if you are using more than one transmitter, or more than four receivers, Non-managed network switches may also limit the performance of other devices connected to the same network.

Certifications, Reports and Compatibility



Applications

- Distribute a separate 3.5 mm audio source and switch between that source and the native HDMI audio source
- Build a multi-display video wall to present entertainment to your patrons with an impressive display at a restaurant or shopping center
- Extend HDMI and RS-232 serial to create an interactive digital signage presentation
- Display multiple communication boards showing dynamic data such as times and dates on digital charts in airports, train stations, bus stations or hospitals, that can be updated at any time
- Present your social media feeds on multiple screens in a large viewing area

Features

- Versatile video distribution with support for large multi-display presentations, video walls, video switching and point-to-point extension
- Astonishing picture quality over IP with support for 4K at 30Hz resolution
- Free mobile app makes it easy to manage switching video wall control (iOS / Android / Chrome browser)
- Tidy, professional installation using the included mounting hardware
- Connect using a Gigabit LAN network
- Easy point-to-point or point-to-multipoint setup
- Extend HDMI using existing network infrastructure

Hardware	Warranty	2 Years
	Audio	Yes
	Cabling	Cat 5e UTP or better
	Daisy-Chain	Yes
	Output Signal	HDMI
	Ports	1
	Rack-Mountable	Yes
Performance	Audio Specifications	Stereo Sound
	Max Distance	100 m / 330 ft
	Maximum Digital Resolutions	4K @ 30Hz
	Supported Resolutions	3840x2160 (4K) @ 30Hz 2560x1600 1920x1200 @ 60Hz 1920x1080 (1080p) 1280x720 (720p)
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - HDMI (19 pin) Female Output 1 - RJ-45 Female 2 - RJ-11 Female 4 - 3.5 mm Mini-Jack (3 Position) Female
Power	Center Tip Polarity	Positive
	Input Current	0.6 A
	Input Voltage	100 ~ 240 AC
	Output Current	1.5 A
	Output Voltage	12 DC
	Plug Type	M
	Power Consumption (In Watts)	18
	Power Source	AC Adapter Included
Environmental	Humidity	0% - 80 %
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-10°C to 60°C (14°F to 140°F)
Physical Characteristics	Color	Black
	Enclosure Type	Aluminum

	Product Height	1.2 in [30 mm]
	Product Length	5.2 in [131 mm]
	Product Weight	21 oz [594 g]
	Product Width	4.6 in [117 mm]
Packaging Information	Shipping (Package) Weight	2.7 lb [1.2 kg]
What's in the Box	Included in Package	<ul style="list-style-type: none"> 1 - HDMI over IP receiver 1 - universal power adapter (NA, EU, UK, ANZ) 1 - mounting bracket 1 - CAT5 cable 1 - RJ11 to RS232 adapter 1 - RJ11 cable 1 - plastic screwdriver 1 - quick-start guide

Product appearance and specifications are subject to change without notice.